


MOLYDUVAL

Bentogen BMN 25



High Temperature Grease

A lubricating grease for bearings in machines working under high working temperatures. Contains inorganic non dropping thickener, is relative unsensitive to wet working conditions, hot and cold water, steam, agressive fluids, acids.

When used at temperatures exceeding 150°C lubricating intervals should be shortened for reducing the risk of grease hardening in the bearing.

Properties

- * high temperature resistance
- * soft and smooth
- * good water resistance
- * non dropping, melting at high temperatures (no dropping point)
- * protects from wear
- * good tackiness
- * withstands weak acids and alkaline solutions
- * relative good compatible with hot glues

Applications

- * for spindles
- * for bearings in high temperature sectors, ventilators, ovens, motors
- * for lubrication of pin ejectors of plastic injection machines
- * for heavy duty sleeve - and anti-friction bearings staying in contact with solvents, gaz, petrol or their vapors
- * for bearings at hot glue application machines
- * for steam faucets
- * for labyrinth seals

Technical Datas

Color		green
Consistency Class NLGI	0,1 mm	2-3
Name		KP2,5N-40
Base Fluid		Min
Thickener		inorganic
Density 15°C	kg/m ³	910
Viscosity Base Fluid, 40°C	mm ² /s	180
Viscosity Base Fluid, 100°C	mm ² /s	14
Temperature Range	°C	-40 -> +150
Temperature Range shortly up to	°C	+220
Corrosion Protection copper	Grade	1
Dropping Point	°C	no

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence.