

# EC Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) (Commission Regulation (EU) 2020/878)

Moralub TZ Spray

Date 09.03.2025 Page 1

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

|   |   |
|---|---|
| 1.1 Product identifier  | Moralub TZ Spray  |
| 1.2 Relevant identified uses of the substance or mixture and uses advised against | Synthetic Metal Working Spray - Only suitable for industrial use. Not suitable for commercial or private use. |
| 1.3 Details of the supplier of the safety data sheet                              | MOLYDUVAL GmbH * Halskestr.6 * 40880 Ratingen * Germany * +49 (2102) 9757-00 * safety@molyduval.info          |
| 1.4 Emergency telephone number  | +49 (2102) 9757-20 (24h)  |

## SECTION 2: Hazards Identification

|   |  |
|---|--|
| 2.1 Classification of the substance or mixture 1272/2008/EG | Hazard Statements / Category of Danger / Hazard class<br>H222 / Aerosol 1 / Extremely flammable aerosol.<br>H229 / Aerosol 1 / Pressurized container: May burst when heated.<br>H412 / Aquatic Chronic 3 / Harmful to aquatic life with long lasting effects.<br>The product is classified acc to 1272/2008/EG |
|---|--|

### 2.2 label elements



signal word: Danger  
GHS02 Extremely flammable  
H222 Extremely flammable aerosol.  
H229 Pressurized container: May burst when heated.  
H412 Harmful to aquatic life with long lasting effects.  
P210 Keep away from heat, sparks, open flames, hot surfaces and other sources of ignition. No smoking.  
P211 Do not spray on an open flame or other ignition source.  
P251 Pressurized container: Do not pierce or burn, even after use.  
P261A Avoid inhalation of aerosol.  
P410+P412 Protect from sunlight and do not expose to temperatures exceeding 50°C.

|                   |  |
|-------------------|--|
| 2.3 Other hazards | In case of insufficient ventilation and / or through use, explosive / highly flammable mixtures. |
|-------------------|--|

## SECTION 3: Composition - Information on Ingredients

### 3.2 Mixtures

Mixture of substances listed below with nonhazardous additions.

20,0 % - 35,0 % Butane EG: 203-448-7 CAS: 106-97-8 H220 Flam. Gas 1 / H280 (MOCLGASB)

5,0 % - 10,0 % Propane EG: 200-827-9 CAS: 74-98-6 H220 Flam. Gas 1 / H280 (MOCLGASP)

5,0 % - 10,0 % Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, aromatics (2-25%) EG: 265-185-4 CAS: 927-510-4 H304 Asp. Tox. 1 / H304 Asp. Tox. 1 / H372 STOT RE 1 / H372 STOT RE 1 / H412 Aquatic Chronic 3 / H412 Aquatic Chronic 3 (MOCLKWC1013NICA25)

5,0 % - 10,0 % Hydrocarbons, C7-C9, n-alkanes, isoalkanes, cyclics EG: 927-750-0 CAS: 64742-49-0 Reach: 01-2119475515-33 H225 Flam. Liq. 2 / H304 Asp. Tox. 1 / H315 Skin Irrit. 2 / H336 STOT SE 3 / H411 Aqua Chron. 2 (MOCLKWC0709NIC)

1,0 % - 3,0 % isobutane EG: 200-857-2 CAS: 75-28-5 Reach: 01-2119485395-27 (MOCLGASIB)

1,0 % - 2,0 % Hydrocarbons, C6, isohexane, < 5% n-hexane EG: 931-254-9 Reach: 01-2119484651-34 H225 Flam. Liq. 2 / H304 Asp. Tox. 1 / H315 Skin Irrit. 2 / H336 STOT SE 3 / H411 Aqua Chron. 2 (MOCLKWC06IH5)

|                            |  |
|----------------------------|--|
| 3.3 Additional information | Substances listed on ECHA's Candidate List of Substances of Very High Concern (SVHC) are not intentional components of this product. It is therefore unlikely that those substances are contained in the product in quantities > 0.1%. |
|----------------------------|--|

## SECTION 4: First Aid Measures

|  |   |
|--|---|
| General Instructions   | Remove victim from danger zone, without exposing yourself to any personal risk. Remove wetted clothing and shoes and clean items before using them again.   |
| After Inhalation   | Remove exposed person to fresh air.   |
| After Skin Contact   | Wash with plenty of soap and plenty of water. Consult a doctor if skin irritation persists.   |
| After Eye Contact  | Long lasting rinse Rinse opened with water, if necessary, use eye wash. If symptoms persist, seek medical advice.   |
| After Ingestion  | Rinse mouth and drink plenty of water. Do not induce vomiting. If symptoms persist, seek medical advice.  |
| Most important symptoms and effects, both acute and delayed                | Difficulty breathing, headache, dizziness, nausea, dry skin.  |
| Indication of any immediate medical attention and special treatment needed | Prolonged and/or repeated exposure may cause skin discomfort and inflammation (dermatitis). In case of swallowing followed by vomiting, material may be aspirated into the lungs - possibly leading to pulmonary edema (wetlung). |

## SECTION 5: Fire-Fighting Measures

|   |   |
|---|---|
| 5.1 Extinguishing media                                   | Suitable extinguishing media : Water spray. Foam. Dry powder. Carbon dioxide (CO2).<br>Unsuitable extinguishing media : Strong water jet.                     |
| 5.2 Special hazards arising from the substance or mixture | In case of a fire, there may arise poisonous (CO, CO2 and other organic gases) gases. Run-off does not allow to enter drains or watercourses by firefighters. |

# EC Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) (Commission Regulation (EU) 2020/878)

## Moralub TZ Spray

Date 09.03.2025 Page 2

### 5.3 Advice for firefighters

If necessary, use in case of fire, self contained breathing apparatus. Collect contaminated firefighting water separately, must not be discharged into drains. Fire residues and contaminated firefighting water must be disposed of in accordance with local regulations. Extinguishing measures to the surroundings. Standard procedure for chemical fires. Extinguishing measures to the surroundings.

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Wear personal protective equipment. Avoid contact with eyes and skin.

### 6.2 Special Environmental Protection

Avoid entering into drains, water courses or soil. Fire or police agree, if the product has escaped into a water course or sewage system, or has contaminated the soil and plants.

### 6.3 Methods and material for containment and cleaning up

Use oil sucking materials f.e chemical absorbents.

### 6.4 Reference to other sections

n.a.

## SECTION 7: Handling and Storage

### 7.1 Precautions for safe handling

Container under pressure. Do not expose to temperatures exceeding 50°C (f.e. sunlight). Do not open violently.

### 7.2 Conditions for safe storage, including any incompatibilities

Storage according to TRG 300. To be stocked cool and dry, protect from sunlight and do not expose to temperatures exceeding 50 degree C. Smoking prohibited.  
Storage Class VCI: 2 B

## SECTION 8: Limiting and supervising the exposure / personal protection

### 8.1 Control parameters

-----  
Butane EG: 203-448-7 CAS: 106-97-8:  
n-Butan (<0,01% Butadien -1,3) 1,928 mg/m<sup>3</sup>, Cat. 4, MAK  
AGW: 2400 mg/m<sup>3</sup>, 1000 ml/m<sup>3</sup>, 4(II);DFG  
-----

Propane EG: 200-827-9 CAS: 74-98-6:  
Propan 1,800 mg/m<sup>3</sup>, Cat. 4, MAK  
-----

Hydrocarbons, C10-C13, n-alkanes, isoalkanes, cycloalkanes, aromatics (2-25%) EG: 265-185-4 CAS: 927-510-4:  
Testbenzin 180/210 C 9-C 15 Aliphaten C9-C15 Aromaten AGW: 350 mg/m<sup>3</sup> Spitzenbegrenzung: 2(II) ASG  
DNEL/ DMEL und PNEC-Werten liegen derzeit nicht vor  
-----

isobutane EG: 200-857-2 CAS: 75-28-5 Reach: 01-2119485395-27:  
AGW Langzeitwert: 2400 mg/m<sup>3</sup>, 1000 ml/m<sup>3</sup>, 4(II);DFG  
-----

Hydrocarbons, C6, isohexane, < 5% n-hexane EG: 931-254-9 Reach: 01-2119484651-34:  
Kohlenwasserstoffe, C6, iso-Alkanen 903 mg/m<sup>3</sup>  
-----

### 8.2 Limitation and supervision of exposure - Personal Protective Equipment

Respiratory protection: Not required, except in case of aerosol formation. Avoid inhalation of vapors. Use respiratory protective device against the effects of fumes / dust / aerosol. Combination filter, eg. As DIN 3181 ABEK  
Hand protection: Gloves - oil resistant. Glove material: nitrile rubber, butyl rubber or fluoro rubber. Recommended thickness: = 0,4 mm. Penetration time of glove material Value for the permeation: Level = 480 min. The determined penetration times according to EN 374 part III are not performed under practical conditions. Therefore a maximum wearing time, which corresponds to 50% of breakthrough time is recommended.  
Eye protection: Safety glasses  
Hygiene measures: Wash hands before breaks and immediately after handling the product. Keep working clothes separately. Take off all contaminated clothing immediately.  
Protective measures: Handle in accordance with good industrial hygiene and safety practice.  
Body protection: work clothes

### 8.3 Delimitation and monitoring of environmental exposure

Do not discharge into surface water or drains

## SECTION 9: Physical and Chemical Properties

|                                 |                               |
|---------------------------------|-------------------------------|
| Appearance Form                 | aerosol                       |
| Color                           | transparent                   |
| Appearance                      | not specified                 |
| Odour                           | like petrol                   |
| Boiling Point / Boiling Range   | -                             |
| Melting Point / Melting Range   | -                             |
| Flash Point                     | < -20 °C TOC                  |
| Autogenous Ignition Temperature | -                             |
| Upper Explosion Limit           | Not applicable                |
| Lower Explosion Limit           | Not applicable                |
| Vapor Density                   | -                             |
| Specific Gravity, 20°C          | 0,95 - 1,05 g/cm <sup>3</sup> |
| Water Solubility                | No                            |
| Viscosity, 40°C                 | -                             |

# EC Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) (Commission Regulation (EU) 2020/878)

## Moralub TZ Spray

Date 09.03.2025 Page 3

Partition Coefficient n-oct/water -  
VOC-Content -

### SECTION 10: Stability and Reactivity

10.1 Reactivity Danger of explosion in case of overheating  
10.2 Chemical Stability Stable under normal conditions  
10.3 Possibility of hazardous reactions No dangerous reaction known under conditions of normal use. Fumes can combine with air to form an explosive mixture.  
10.4 Conditions to be avoided No information available  
10.5 Incompatible Materials no information available  
10.6 Hazardous products of instability / decomposition no

### SECTION 11: Toxicological Information

Symptoms after ingestion May cause sickness and vomiting.  
At Skin Contact No hazard.  
Symptoms after Inhalation no data available  
Symptoms after eye contact No hazard.  
Other information No sensitizing effects known.  
Toxicological Tests There are no human toxicological data.  
Further Toxicologic Effects The product is classified acc to 1272/2008 [CLP]

### SECTION 12: Ecological Information

12.2 Persistence and degradability Ecotoxicological data have not been determined specifically for this product. The information provided is based on the knowledge of the components. Product is not readily biodegradable. The main constituents are expected to be inherently biodegradable, but some components that may persist in the environment.  
12.3 Bioaccumulative potential not information available  
12.4 Mobility in soil No information available  
12.5 Results of PBT and vPvB assessment No information available  
12.6 Endocrine disrupting properties No information available  
12.7 Other adverse effects No information available

### SECTION 13: Disposal Considerations

13.1 Waste treatment methods Waste key for uncleaned packing: 150110 PACKING WASTE, ABSORPTION MASSES, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING (A. n. g.); Packing (separated including collect locally Packing wastes); Packing, which is polluted by dangerous materials arrears of dangerous materials contained or ss dangerous waste classified.

### SECTION 14: Transport information in accordance with ADR / RID / ADNR / IMDG / ICAO / IATA

14.1 UN-No 1950  
14.2 UN proper shipping name CLASS 2 CODE 5F CODE: 1950 AEROSOLS FLAMMABLE, LIMITED QUANTITIES (LQ2)  
14.3 Transport hazard class 2.1  
Danger label: 2.1  
Special Provisions: A145 A167 A802  
Limited Quantity (LQ) Passenger: 30 kg G  
IATA Packing Instruction – Passenger: 203  
IATA Maximum Quantity – Passenger : 75 kg  
IATA Packing Instruction – CARGO: 203  
IATA Maximum Quantity - CARGO: 150 kg  
Other applicable information about air transport  
Exempted quantity: E0  
Passenger-LQ: Y203  
14.4 Packing group No  
14.5 Environmental hazards Non-hazardous to the environment in tankers  
14.6 Special precautions for user No information available  
14.7 Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code No information available

### SECTION 15: Regulatory Information

15.1 Safety, health and environmental regulations / legislation specific for the substance or mixture DE: water polluting category: 1  
DE: Employment restrictions concerning juveniles must be observed (§ 22 JArbSchG).

15.2 Chemical safety assessment There is no information available

### SECTION 16: Further Information

# EC Safety Data Sheet according to Regulation (EC) No. 1907/2006 (REACH) (Commission Regulation (EU) 2020/878)

Moralub TZ Spray

Date 09.03.2025 Page 4

16.1 Full text of the dangers in section 2 and 3

- GHS02 Extremely flammable
- H222 Extremely flammable aerosol.
- H229 Pressurized container: May burst when heated.
- H412 Harmful to aquatic life with long lasting effects.
- P210 Keep away from heat, sparks, open flames, hot surfaces and other sources of ignition. No smoking.
- P211 Do not spray on an open flame or other ignition source.
- P251 Pressurized container: Do not pierce or burn, even after use.
- P261A Avoid inhalation of aerosol.
- P410+P412 Protect from sunlight and do not expose to temperatures exceeding 50°C.

## 16.2 Further Information

The information in this SDS is correct to the best of our knowledge at the time of its publication. The information is intended to give you advice about the safe handling of the product named in this safety during storage, processing, transport and disposal. The details are not transferable to other products. The information given in this safety combination with any other materials or in any process, or undergoes processing, can use the information in this SDS, to the extent that it does not specifically indicate otherwise, are not transferred to the new made material. The material data referred to in item 9 are safety information, but no guarantees on properties. Warranties are excluded without clarification of the technical intended use and the operating conditions. If you have further questions we are available.