

MOLYDUVAL

AntiStatik Spray



Anti Static Spray with Cleaning Properties

Eliminates the impact effect and lifts the attraction of dust and plastic fibers. Such materials become electro-statically, will attract dust and get dirty quickly.

Characteristics

- evaporates residue-less
-

Applications

-
-
- for printings machines, f.e. paper trays
-

Technical Datas

Color		Undefined
Temperature Range	°C	-50 -> +220
Pack Size spray can		400 ml +

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 31.01.2025