


MOLYDUVAL

Ferroxin DE Spray



Biodegradable Wire Rope Spray

A modern preservation and care spray for wire ropes, penetrates the rope and lubricates the strands, forming an adhesive, oily layer on the surface of the wire rope. The selection of special, highly effective raw materials ensures good adhesion, homogeneity and uniformly thick film formation.

Characteristics

- free of graphite
- relative good resistant against alkaline fluids and gases
- free of bituminous materials
- neutral to metal surfaces
- good tackiness
- very economic
- relative good compatibility with seals, plastics and paints, please check compatibility before application

Applications

- for protection of steel tubes and profiles at outside storage
- for preservation of machines, gear boxes, turbines, vehicles, agricultural equipment
- for conservation and lubrication of wire ropes
- for wire ropes at cranes, container appliances, open cast mining appliances and excavators

Technical Datas

Color		Color transparent
Basis		ester
Viscosity Class	ISO-VG	46
Viscosity 40°C	mm ² /s	46
Viscosity 100°C	mm ² /s	8
Viscosity Index		125
Density 40°C	kg/m ³	950
Temperature Range	°C	-40 -> 270
Pour point	°C	-46
Pack Size spray can 400 ml		+
Customs tariff number		340399

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.