



MOLYDUVAL

Gloria B 70



Swabbing Compound

Swabbing Lubricant containing graphite, sulphure and other additives for hollow glass packaging.

Properties

- * low smoke formation
- * resistant to water
- * good moistening
- * long using times
- * high rub resistance
- * minimum transfer of graphite
- * easy loading of swabs

Applications

- * as release agent for moulds in glass industry

Instructions

Should be used with a dry swab. A light dipping of the swab is recommended. Excess lubricant must be squeezed out before applying to the mold equipment.

Technical Datas

Color		black
Density 15°C	kg/m ³	920
Flash Point PMCC, base oil	°C	240
Content graphite	%	5,6
Content sulphur	%	4,5

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 27.01.2021