



MOLYDUVAL

Sekorex ETT Spray



Synthetic Chain Lubricant Spray

Lubricant with PTFE for high loads, suitable for chains, hinges, joints, wire parts, etc. Penetrates very well in chains and wire ropes. In addition to excellent high-temperature stability, it offers very good wear protection and good corrosion protection.

Characteristics

- very high pressure ability
- compatible with mineral oil
- free from mineral oil
- low smoke formation
- biodegradable
- low evaporation
- good low temperature characteristics
- low residues
- low noise
- high flash point
- good ageing resistance
- harmless
- PTFE solid lubricant share offering additional friction reducing
- low residue forming
- strong tackiness caused by very long molecules
- penetrates between the clearance of chain drive

Applications

- for chains in high temperature sectors
- for chains in food industry, for packing and filling machines
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for motorcycle chains
- for chains in drying ovens, painting ovens, baking ovens, e.g. in the production of plasterboard and chipboard as well as glass or rock wool
- for linear guides at cranes

Technical Datas

Color		yellow
Basis		ester
Viscosity Class	ISO-VG	320
Viscosity Index		150
Density 20°C	kg/m ³	1000
Temperature Range	°C	-20 -> 230
Pour point	°C	< -27
Pack Size spray can 400 ml		+
Customs tariff number		340399

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.