


MOLYDUVAL

Sekorex H Spray



Synthetic Chain Lubricant Spray

A 100% synthetic ester based, very tacky lubrication oil for high temperature chains. Besides of it's excellent high temperature stability it guarantees excellent wear protection and good corrosion protection. Qualified for chains and even suitable for bearings, slides and sliding surfaces at high temperatures. In case of very high temperatures it forms only less residues, and evaporates low.

Characteristics

- very high pressure ability
- compatible with mineral oil
- free from mineral oil
- low smoke formation
- very good tackiness
- low evaporation
- good low temperature characteristics
- low residues
- low noise
- high flash point
- good ageing resistance
- harmless
- low residue forming
- strong tackiness caused by very long molecules
- penetrates between the clearance of chain drive

Applications

- for chains in high temperature sectors
- for chains in food industry, for packing and filling machines
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for motorcycle chains
- for chains in drying ovens, painting ovens, baking ovens, e.g. in the production of plasterboard and chipboard as well as glass or rock wool

Technical Datas

Color		transparent
Base Fluid		ester
Name		ELP680
Viscosity Base Fluid, 40°C	mm ² /s	680
Density 40°C	kg/m ³	920
Temperature Range	°C	-30 -> +260
DB 075.51		+
USDA H2		+
Pack Size spray can 400 ml		+

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.