



MOLYDUVAL

Sekorex IL Spray



Chain Drive Pin Lubricant

A high treated low viscosity penetrating oil for chains. Penetrates between the close clearance of the chain drive bushings and pins to provide lubrication. For chains in assembly lines, machinery, fork lifts, conveyers.

Characteristics

- free of silicones
- excellent wear protection
- good low temperature characteristics
- low volatility, evaporates extremely slowly
- extremely high penetrative properties
- low viscosity
- good ageing resistance
- infiltrates humidity
- very thin film
- good penetrative properties
- penetrates between the clearance of chain drive
- cleans the chain, looses dirt

Applications

- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for chains in precision engineering
- for bicycle chains

Technical Datas

Color		brown
Density 15°C	kg/m ³	830
Temperature Range	°C	-30 -> +80
Pour point	°C	-60
Flash Point COC	°C	63

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 15.01.2024