



MOLYDUVAL

Sekorex ILM Spray



Heavy Duty Low Viscous Lubricant for Chains

High treated lubrication oil spray for chains, especially for heavy duty or outside door chains. Because of its good creeping characteristics it penetrates very good into the chain bolts and reduces wear. Molybdenum Disulphide provides extra protection against friction and wear. The MoS₂ smooth surfaces and improves pressure load.

Characteristics

- exceptional lubricating and separating properties
- good pressure absorption capacity
- strong tackiness
- relative good compatible with elastomers and seals
- provides protection against corrosion
- friction reducing caused by forming solid MoS₂ film
- excellent wear protection
- rejects dirt

Applications

- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for wire ropes at cranes, container appliances, open cast mining appliances and excavators
- for motorcycle chains
- for chains on bouw machines, lifters, mills

Technical Datas

Color		black
Base Fluid		Min
Viscosity Class	ISO-VG	150
Viscosity 40°C	mm ² /s	126
Viscosity 100°C	mm ² /s	13
Viscosity Index		100/150
Density 40°C	kg/m ³	930
Temperature Range	°C	-20 -> 120
Pour point	°C	-21
Flash Point COC	°C	270
Pack Size spray can 400 ml		+

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.