

MOLYDUVAL

Sekorex MHV Spray



A very tacky, high treated lubrication oil spray for chains, especially for outside door chains. Because of its good creeping characteristics it penetrates very good into the chain bolts and reduces wear. O-Ring compatible. Contains tackifiers for better adhesion on fast running chains.

Characteristics

- exceptional lubricating and separating properties
- good pressure absorption capacity
- strong tackiness
- relative good compatible with elastomers and seals
- provides protection against corrosion
- excellent wear protection
- rejects dirt

Applications

- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for chains in textile industry
- for wire ropes at cranes, container appliances, open cast mining appliances and excavators
- for motorcycle chains
- for chains on bouw machines, lifters, mills
- for chains in sensitive areas
- for saw chains on high-speed motor and electric saws
- for chains and wire ropes on ships

Technical Datas

Color		black
Base Fluid		Min
Name		CLP4600
Viscosity 40°C	mm ² /s	4600
Density 15°C	kg/m ³	910
Temperature Range	°C	-20 -> + 140
Pack Size spray can 400 ml		+
Customs tariff number		340399

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.