



# MOLYDUVAL

## Sekorex PLX Spray



### Synthetic Chain Lubricant with MoS<sub>2</sub>

An very adhesive chain lubricant for very high loaded, slow running chains. Because of its good water resistance and oxidation stability it is even useful under corrosive conditions. It is a black grease containing the solid molybdenum disulphide for reduced friction and emergency run properties.

### Characteristics

- good anticorrosive properties
- exceptional lubricating and separating properties
- prevents seizure and rust
- very high pressure ability
- reduces risk of tribo corrosion
- reduced friction coefficient with increasing pressure
- reduces wear and friction
- reduces risk of Stick-Slip-effect
- reduces friction in running in phase
- very good tackiness
- resistant to water
- offers emergency running property
- dust refusing, rejects dust and dirt

### Applications

- for open gears
- for chains in high temperature sectors
- for chain lubrication in dusty surroundings
- for chains in textile industry
- for chains on bouw machines, lifters, mills
- for wire ropes in power plants
- for chains at energy plant, f.e. chains of burner cleaning equipment

### Technical Datas

|                                                      |    |              |
|------------------------------------------------------|----|--------------|
| Color                                                |    | black        |
| Base Fluid                                           |    | Syn          |
| Temperature Range                                    | °C | -25 -> + 200 |
| Temperature Range dry lubrication, solid lubrication | °C | 450          |
| Pack Size spray can 400 ml                           |    | +            |

*The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.*