


MOLYDUVAL

Tantalus ET 1500



Synthetic High temperature Gear Oil

A very high additive, fully synthetic, very thick special gear oil with special, wear-protecting active ingredients that smooth the surfaces of gears. Offers reliable protection for low-speed gears when conventional gear or gear lubricants are insufficient due to their viscosity or temperature resistance. Suitable for the lubrication of almost all types of closed industrial gears with spur, bevel or worm gears for splash and circulating lubrication, also for plain and roller bearings, joints, guides.

Characteristics

- strong extreme pressure treatment
- reduces anti seizing
- excellent wear protection
- long usability due to good oxidative resistance
- form surface active molecular protection films
- low foam
- relative good compatibility with seals, plastics and paints, please check compatibility before application

Applications

- for circulating systems, even under heavy loads and/or the most unfavorable operating conditions
- for high temperature gears
- for enhance running-in lubrication of bearings, guidelines and gears
- for industrial gears and thread spindles running slowly but loaded heavy
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for industrial gear boxes working under high temperatures, or other unfavorable conditions

Technical Datas

Color		brown
Base Fluid		ester
Viscosity 40°C	mm ² /s	ca. 1500
Viscosity Index		130
Density 40°C	kg/m ³	920
Temperature Range	°C	-0 -> +260
Pour point	°C	-20
Flash Point COC	°C	> 200
Pack Size can 5 l		+
Pack Size drum 200 l		+

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 11.03.2025