

MOLYDUVAL

Tantalus M 32 T



Special PTFE Oil

PTFE containing, high treated lubrication oil for heavy loads. Contains Polyterafluoroethylene for reduced friction and emergency lubrication. The microfine particles smoothe surfaces and increase metal treatment properties. It's a relatively stable suspension, settling down could be returned by easy mixing.

Characteristics

- good anticorrosive properties
- protects against rust and tribo corrosion
- oxidation resistant
- compatible with mineral oil
- reduces wear and friction
- good lubrication performance

Applications

- for circulating systems, even under heavy loads and/or the most unfavorable operating conditions
- for chains
- for high temperature gears
- for enhance running-in lubrication of bearings, guidelines and gears
- for industrial gears and thread spindles running slowly but loaded heavy
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for industrial gear boxes working under high temperatures, or other unfavorable conditions
- for industrial gear boxes
- for gears in textile industry

Technical Datas

Color		beige
Name		CLPF32
Viscosity 40°C	mm ² /s	32
Density 40°C	kg/m ³	890
Temperature Range	°C	-15 -> +150
Pour point	°C	-30
Flash Point COC	°C	160
Fineness Ø	µm	Min
Pack Size can 5 l		+ > 100l
Pack Size drum 200 l		+
Customs tariff number		271019

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.