



MOLYDUVAL

Tantalus T 32



Special Lubrication Fluid with PTFE

PTFE containing, high treated lubrication oil for heavy loads. Contains Polyterafluoroethylene for reduced friction and emergency lubrication. The microfine particles smoothe surfaces and increase metal treatment properties. It's a relatively stable suspension, settling down could be returned by easy mixing.

Characteristics

- good anticorrosive properties
- protects against rust and tribo corrosion
- oxidation resistant
- compatible with mineral oil
- reduces wear and friction
- good lubrication performance

Applications

- for circulating systems, even under heavy loads and/or the most unfavorable operating conditions
- for chains
- for high temperature gears
- for enhance running-in lubrication of bearings, guidelines and gears
- for industrial gears and thread spindles running slowly but loaded heavy
- for chains, drive and transport chains, in conveying machines, pasteurize plants, sorting stations, peelers, packing and labelling machines, shrinking tunnels
- for industrial gear boxes working under high temperatures, or other unfavorable conditions
- for industrial gear boxes
- for gears in textile industry

Technical Datas

Color		beige
Name		CLPF32
Viscosity 40°C	mm ² /s	32
Density 40°C	kg/m ³	890
Temperature Range	°C	-15 -> +150
Pour point	°C	-30
Flash Point COC	°C	160
Fineness Ø	µm	Min
Pack Size can 5 l		+

The indicated service temperatures are guide values depending on the lubricants composition and on the application. They may vary in case of special influences or ongoing use.

For further information, please see our website www.molyduval.com or consult your local representative.

The content of this manual is based on our current knowledge and experience in the development and manufacture of lubricants. Because of the complexity of tribological systems, the effect of our products depends on many parameters, which we cannot assess and which influence we cannot evaluate. For this reason general statements about the function of our products are not possible. The information in this manual, therefore, contains non-binding guidelines, which should give the technical trained reader information on possible applications. The information in this manual does not include property assurances or warranties or guarantees to the properties or suitability of this product in a specific application. Prior to its use it is absolutely necessary to test this product in the application to ensure that the product and its use is safe, economical and fully suitable. It should proceed with due diligence. We reserve the right to change the information in this manual at any time and without notice. All previous versions of this manual are no longer valid. Updating : 21.10.2024